Certificate No.: 2531-CPR-CSP10881



CERTIFICATE OF CONSTANCY OF PERFORMANCE

Issued by DBI Certification, notified body No. 2531.

In compliance with Regulation 305/2011/EU of the European Parliament and of the Council of 9 March 2011 (the Construction Products Regulation or CPR), this certificate applies to the construction product

55000-122 Series 65 Conventional Class A1R Heat Detector

The product fulfils the essential characteristic:

See Annex 1

Intended use: Applications related to automatic fire alarm systems

Placed on the market under the name or trade mark of:

Apollo Fire Detectors Limited
36 Brookside Road, Havant, Hampshire, PO9 1JR, UK

and produced in the manufacturing plant:

Apollo Fire Detectors Limited
36 Brookside Road, Havant, Hampshire, PO9 1JR, UK

This certificate attests that all provisions concerning the assessment and verification of constancy of performance described in Annex ZA of the standards

EN 54-5:2000/A1:2002 : Fire detection and fire alarm systems - Part 5: Heat detectors - Point detectors

under system 1 for the performance set out in this certificate are applied and that the performance of the construction product is assessed to remain constant.

The attached annexes form part of this certificate.

Date of issue: 2019-10-09

This certificate will remain valid as long as neither the harmonized standard, the construction product, the AVCP methods nor the manufacturing conditions in the plant are modified significantly unless suspended or withdrawn by the notified product certification body.

This certificate was first issued 2019-10-09

Merete Poulsen Responsible for evaluation

Allan Laursen
Responsible for certification decision



Certificate No.: 2531-CPR-CSP10881





Annex 1

EXTENT

Type:

55000-122 Series 65 Conventional Class A1R Heat Detector

Variant

55000-122LIM (branded as Limotec)

Bases:

45681-200 Series 60/65 Mounting Base

45681-201 Series 60/65 Diode Mounting Base

45681-245 Series 65 Relay Mounting Base

45681-246 Series 65 Auxiliary Relay Mounting Base

45681-247 Series 65 EOL 12 Volt Mounting Base

45681-248 Series 65 EOL 24 Volt Mounting Base

Noto:

1. Meets the requirements of EN54: Part 5 - Class A1R

Performance

Essential characteristics	Clauses in EN 54-5:2000		Performance
Nominal activation	4.2, 4.3, 5.2 to 5.6, 5.8, 6.1, 6.	2	Pass
conditions/Sensitivity, Response	(6.1 only Suffix S det./6.2 only Suffix		
delay (response time) and	R det.)		
Performance under fire conditions			
Operational reliability	4.4 to 4.11		Pass
Tolerance to supply voltage	5.7		Pass
Durability of operational reliability	5.9, 5.10		Pass
and response delay; temperature			
resistance			
Durability of operational reliability;	5.14 to 5.17		Pass
vibration resistance			
Durability of operational reliability;	5.11, 5.12		Pass
humidity resistance			
Durability of operational reliability;	5.13		Pass
corrosion resistance			
Durability of operational reliability;	5.18		Pass
electrical stability			



Certificate No.: 2531-CPR-CSP10881





Annex 2

TEST DOCUMENTATION

Accredited Laboratory	Report no.	Date
BRE VdS	P100476-1001 Issue: 1 BMA 00018	30 March 2016 3 March 2000

TECHNICAL BASIS

TECHNICAE BASIS	
File Number	Title
55000-122 45681-200 45681-201 45681-245 45681-246 45691-247 45681-248	Build Standard

